

3-Phase Diode Bridge

DF30CA80/160

UL; E76102



《Features》

Power Diode Module DF30CA is designed for three phase full wave rectification, which has six diodes connected in a three phase bridge configuration. The mounting base of the module is electrically isolated from semiconductor elements for simple heatsink construction output DC current is 30Amp (Tc=122°C) Repetitive peak reverse voltage is up to 1,600V.

- IFSM=775/850A (50/60Hz)
- TjMax=150°C
- Isolated Mounting Base
- High reliability by unique glass passivation
- Easy Assemble by the #250 terminal Tab

《Applications》

- AC. DC Motor Drive / AVR / Switching — for three phase rectification



■ Maximum Ratings (Tj=25°C unless otherwise specified)

Item	Symbol	Unit	DF30CA80	DF30CA160
Repetitive Peak Reverse Voltage	V_{RRM}	V	800	1600
Non-Repetitive Peak Reverse Voltage	V_{RSM}	V	960	1700

Item	Symbol	Unit	Ratings	Conditions
Output Current(D.C.)	I_D	A	30	$T_C=122^\circ\text{C}$
Surge Forward Current	I_{FSM}	A	775/850	1/2cycle,50/60Hz,Peak value,non-repetitive
Operating Junction Temperture	T_j	°C	-40 to +150	
Storage Temperature	T_{stg}	°C	-40 to +125	
Isolation Breakdown Voltage(R.M.S.)		V	2500	A.C.1 minute
Mounting torque	Mounting M6	N·m (kgf·cm)	4.7(48)	Recommended Value 2.5 to 3.9 (25 to 40)
	Mounting M5			
Mass		g	90	Typical

■ Electrical Characteristics (Tj=25°C unless otherwise specified)

Item	Symbol	Unit	Ratings			Conditions
			Min.	Typ.	Max.	
Repetitive Peak Reverse Current	I_{RRM}	mA			12	$T_j=150^\circ\text{C}$ at V_{RRM}
Forward Voltage Drop	V_{FM}	V			1.1	Forward current 30A
Threshold Voltage	$V_{(TO)}$	V			0.85	$T_j=150^\circ\text{C}$
Dynamic Resistance	r_t	mΩ			3.8	$T_j=150^\circ\text{C}$
Thermal Resistance	$R_{th(j-c)}$	°C/W			0.42	Junction to case per module
Interface Thermal Resistance	$R_{th(c-f)}$	°C/W			0.1	Case to Heat Sink Thermal conductivity(Silicon grease) $\cong 7 \times 10^{-3} [\text{W}/\text{cm} \cdot ^\circ\text{C}]$

